

# COST-EFFECTIVE CELLULAR ELEVATOR COMMUNICATIONS WITH DEPENDABLE CODE-COMPLIANT TECHNOLOGY



Reduce phone line expenses with Cellevator!

Cellevator is a dependable, code-compliant two-way cellular voice communicator for elevators. Replace existing and expensive traditional phone lines with Cellevator wireless emergency monitoring.

Cellevator is also an excellent cost-effective solution for Area of Refuge Assistance, Two-Way-In-Building communications systems, pool phones, and other communicators requiring telephone voice communications.

Since 2009, customers have relied on Cellevator to provide two-way voice communication in existing as well as new elevators. Many new buildings don't have analog phone lines, enhancing the need for a wireless, point-of-service product like Cellevator.

Cellevator installation is quick and easy, connecting your elevator's voice path to one of many LTE towers. Cellevator provides a minimum 24-hour dedicated battery backup and a minimum 4 hours talk time, meeting or exceeding ASCME 17 requirements for emergency two-way voice communication in the event of a power outage.

# **TECHNICAL SPECIFICATIONS**

- Verizon LTE technology
- 16.5 Volt Primary Voltage
- Connects to existing Elevator, emergency two-way in building communication systems, pool phones, and areas of rescue assistance
- Supports Caller ID
- Single Strength Indicator
- Adjustable Volume Gain
- Includes 5dB Antenna
- Consumes less than 2 watts
- Can be installed on elevator cab
- LTE communicator is FCC-approved, UL-listed

# **OPTIONS**

- √ Hardwired or wall plug-in transformer
- √ High-gain LTE and GPS antennas
- ✓ Power supply with AC-power and low-battery supervision relays
- √ Fire-Alarm powered configuration
- ✓ Central Station monitoring flexibility

# **PRODUCT FEATURES**

- 24 hour battery backup time with a minimum of 4 hours talk time
- More cost effective than traditional phone lines
- Easy and simple installation process
- Installs near your existing telephone interface
- Dependable and well-built technology with available monitoring
- Excellent customer service! (Ditch the phone companies)





### **OPTIONS**

#### **External Antenna**



External LTE antenna with mount or bulkhead mount to NEMA box. Omni-Directional Multi-band Antenna operates in the 902-928 MHz band.

#### **Supervised Power**



Single Output Power Supply/ Charger that converts a low voltage AC input into a PTC protected 12VDC or 24VDC output.

#### **Hardwired Transformer**



AC power supply provides power for electronic power supplies and equipment including security and access control devices.

# 10 and 20ft external antenna cables



Low loss LMR200 Antenna Cable: N-type male connector to SMAmale Connector.

## **AIRTIME**

Keep your own monitoring or Cellevator can provide remote monitoring for your elevator, Area-of-Rescue Assistance or Two-Way In Building Communications System for your elevator lobbies. We make it simple! One-year Verizon voice-over-LTE airtime for each line. Airtime for each phone line includes up to 500Mb data per month in the base plan.





Replace your elevator phone lines with cellular and save a fortune! Our products reduce customer costs 70% on average.